

ANNEXURE - IX

PRELIMINARY DESIGN OF SPILLWAY

Ogee Shaped Spillway

The discharge over an ogee crest is given by the formula

$$Q = CLH_d^{3/2}$$

Where Q = discharge in cumec or cusec

C = discharge coefficient which is influenced by a number of facts such as

- (1) The depth of approach
- (2) relation of actual crest shape to ideal nappe shape
- (3) upstream face slope
- (4) downstream apron interference
- (5) Downstream submergence

H_d = Total head on the crest, including velocity of approach head

h_a = Reservoir level - crest level + $V_a^2 / 2g$

L = Effective length of crest

Pier and abutment Effects

The effect of end contractions may be taken into account by reduction the net crest length as follows:-

$$L = L - 2(NK_p + K_a) H_d$$

Where L = Net length of crest; N = Number of piers

K_p = Pier contraction coefficient, 0.2 for square abutment and 0.01 for round abutment.

K_a = abutment contraction coefficient, 0.2 for square abutment and 0.01 for round abutment.

HIGH OVER FLOW SPILLWAY WATER SURFACE PROFILES

	WITHOUT PIPES			CENTER LINE OF GATE BAY			ALONG PIERS		
H/Hd	0.50	1.00	1.33	0.50	1.00	1.33	0.50	1.00	1.33
H/Hd	Y/Hd			Y/Hd			Y/Hd		
-1	-0.490	-0.933	-1.21	-0.482	-0.941	-1.230	-0.495	-0.950	-1.235
-0.8	-0.484	-0.915	-1.185	-0.480	-0.932	-1.215	-0.492	-0.910	-1.225
-0.6	-0.475	-0.893	-1.151	-0.472	-0.913	-1.194	-0.490	-0.932	-1.209
-0.4	-0.460	-0.865	-1.110	-0.457	-0.890	-1.165	-0.482	-0.930	-1.218
-0.2	-0.425	-0.821	-1.060	-0.431	-0.855	-1.122	-0.440	-0.925	-1.244
0.0	-0.371	-0.755	-1.000	-0.384	-0.805	-1.071	-0.383	-0.779	-1.103
0.2	-0.300	-0.681	-0.919	-0.313	-0.735	-1.015	-0.265	-0.651	-0.950
0.4	-0.200	-0.586	-0.821	-0.220	-0.647	-0.944	-0.185	-0.545	-0.821
0.6	-0.075	-0.465	-0.705	-0.088	-0.539	-0.847	-0.076	-0.425	-0.689
0.8	0.075	-0.320	-0.569	-0.075	-0.389	-0.725	0.060	-0.285	-0.549
1.0	0.258	-0.145	-0.411	-0.257	-0.202	-0.564	0.240	-0.121	-0.389
1.2	0.470	0.055	-0.220	0.462	0.015	-0.356	0.445	0.067	-0.215
1.4	0.705	0.294	-0.002	0.705	0.266	-0.102	0.675	0.286	0.011
1.6	0.972	0.563	0.243	0.977	0.521	0.172	0.925	0.521	0.208
1.8	1.269	0.857	0.531	1.278	0.860	0.465	1.177	0.779	0.438

DOWN STREAM QUADRANT DATA

X	$X^{1.85}$	X	$X^{1.85}$	Hd	$2Hd^{0.85}$	Hd	$2Hd^{0.85}$
0.1	0.014	3	7.633	0.5	1.11	10.5	14.758
0.15	0.03	3.5	10.151	1	2	11	15.354
0.2	0.151	4	12.996	1.5	2.83	11.5	15.945
0.25	0.077	4.5	16.16	2	3.605	12	16.535
0.3	0.108	5	19.638	2.5	4.358	12.5	17.112
0.35	0.143	6	27.515	3	5.088	13	17.696
0.4	0.184	7	36.596	3.5	5.801	13.5	18.273
0.45	0.228	8	46.851	4	6.498	14	18.847
0.5	0.277	9	58.257	4.5	7.182	14.5	19.417
0.6	0.389	10	70.795	5	7.855	15	19.985
0.7	0.52	12	99.194	5.5	8.518	15.5	20.58
0.8	0.662	14	131.928	6	9.172	16	21.112
0.9	0.823	16	168.897	6.5	9.818	16.5	21.671
1	1	18	210.017	7	10.46	17	22.229
1.2	1.401	20	255.215	7.5	11.087	17.5	22.783
1.4	1.864	25	385.646	8	11.713	18	23.335
1.6	2.386	30	540.349	8.5	12.332	18.5	23.885
1.8	2.967	35	718.664	9	12.946	19	24.433
2	3.605	40	920.049	9.5	13.555	19.5	24.978
2.5	5.447			10	14.159	20	25.521

CO-ORDINATES FOR UPSTREAM QUADRANT

X/Hd	Y/Hd	X/Hd	Y/Hd
0.0000	0.0000	-0.2000	0.0494

-0.0200	0.0004	-0.2100	0.0556
-0.0400	0.0016	-0.2200	0.0624
-0.0600	0.0038	-0.2300	0.0701
-0.0800	0.0068	-0.2400	0.0787
-0.1000	0.0108	-0.2450	0.0836
-0.1200	1.0158	-0.2500	0.0889
-0.1400	0.0221	-0.2550	0.0948
-0.1600	0.0296	-0.2600	0.1016
-0.1700	0.0339	-0.2650	0.1099
-0.1800	0.0386	-0.2680	0.1165
-0.1900	0.0437	-0.2700	0.1260

According to the latest analytical study of U.S. Army the upstream curve of the ogee shape has an equation as below

$$Y = \frac{0.724(X+0.270H_d)^{1.85} + 0.126H_d - 0.4315H_d^{0.375} (X+0.270H_d)^{0.625}}{H_d^{0.85}}$$